



R66B6



R891S



R89B

Description

Emerson Communications offers a line of brackets for mounting a specific series of R66 quick-clip terminal blocks, in either wall or frame environments. Manufactured with UL 94 V-0 rated self-extinguishing thermoplastic, The blocks clamp to the bracket with a snap action. The bracket is also used for routing cables and breaking out wires for more manageable wire routing.

R891S Stand-off Bracket – used with the M series quick-clip terminal blocks. The open design of the R89 bracket allows cable to be positioned before snapping the R66M1-type block into place. There are two mounting holes located in the center of the bracket, which are used when mounting on frames with pre-drilled holes or when the mounting flanges cannot be used.

R89B – predecessor of the R891 stand-off bracket, this bracket cannot be used with blocks that have wire-wrap pin termination. They can be used specifically with the R66M125 and R66M150 connecting blocks.

R66B6 Stand-off Bracket – used with the R66B series quick-clip terminal blocks. It is open at the ends so the bracket may be mounted and running cable laid on before snapping the block into place. It does not have mounting flanges, but has three mounting holes at each end, one in the center and two on 1.75-in. centers.

Ordering Information & Dimensions

| Catalog Number | Part Number | Description | Unit of Measure | H | W | D |
|----------------|-------------|--|-----------------|---------|-------|--------|
| R891S10 | F1004071 | Stand-off mounting bracket for R66 “M” blocks* | 10 | 10" | 2.75" | 1.875" |
| R891S50 | F1003918 | Stand-off mounting bracket for R66 “M” blocks* | 50 | 10" | 2.75" | 1.875" |
| R891S100 | F1004072 | Stand-off mounting bracket for R66 “M” blocks* | 100 | 10" | 2.75" | 1.875" |
| R89B | F015410 | Original style R891 stand-off bracket* | 50 | 10" | 2.75" | 1.875" |
| R89BX | F015411 | R89B bulk pack* | 100 | 10" | 2.75" | 1.875" |
| R66B6 | F015030 | Stand-off mounting bracket for R66 “B” blocks | 1 | 13.375" | 2.75" | 2.125" |

* UL Listed 94 V-0 rated self-extinguishing material.

Emerson Network Power.

The global leader in enabling business-critical continuity.

- AC Power
- Embedded Power
- Precision Cooling
- Connectivity
- Monitoring
- Racks & Integrated Cabinets
- DC Power
- **Outside Plant**
- Services
- Embedded Computing
- Power Switching & Controls
- Surge Protection

Emerson Network Power Energy Systems
 4350 Weaver Parkway, Warrenville, IL 60555
 Toll Free: 800-800-1280 (USA and Canada)
 Telephone: 440-246-6999 Fax: 440-246-4876
 EmersonNetworkPower.com/OSP

© 2007 Emerson Network Power Energy Systems, North America, Inc. All rights reserved.
 The Emerson logo is a trademark and a service mark of Emerson Electric Co. Emerson Network Power is a division of Emerson Electric Co.
 Printed in USA

